

DH-SD5A245XA-HNR

2MP 45x Starlight IR Network PTZ Camera



Wiz Sense

Launched by Dahua Technology, WizSense is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense provides intelligent, simple and inclusive products and solutions.

System Overview

Unique and elegant, the black semicircular sphere discreetly monitors from a distance without drawing undue attention to itself. It has a powerful optical zoom, and accurate pan, tilt and zoom capabilities, providing an all-in-one solution for long distance video surveillance of outdoor scenes. Together with infrared illumination and Starlight Technology, the camera is a great solution for dark, low light conditions. The series combines a day and night mechanical IR cut filter to produce high quality images in variable lighting conditions during the day, and True WDR for locations with direct sunlight and glare.

Functions

Starlight Technology

With advanced image processing technology and optical technology, Dahua Starlight technology can provide clear colorful video in the environment of low illuminance. It widely applies to various environments of low illuminance.

Perimeter Protection

Automatically filters out false alarms caused by animals, rustling leaves, bright lights, and more, and uses secondary recognition during target detection to improve alarm accuracy.

Face Detection

Supports 6 attributes and 8 expressions: Gender, age, glasses, face mask, beard and expressions (anger, sadness, disgust, fear, surprise, calm, happiness, and confusion). It also supports face cutout settings: Face, and single inch photo. Three snapshot methods are also featured: Real-time snapshot, priority snapshot, and quality priority.

- 1/2.8" 2Megapixel STARVIS™ CMOS.
- 45x optical zoom.
- Starlight technology.
- Max. 25/30fps@1080P.
- IR distance up to 150 m.
- Auto-tracking 3.0.
- Perimeter protection.
- Face detection.
- SMD 4.0.
- Quick Pick.
- IP67, IK10.



Auto-tracking

This feature controls the pan/tilt/zoom actions of the camera to automatically track an object in motion and to keep it in the scene. The tracking action can be triggered manually or automatically by defined rules. Once a rule is triggered, the camera can zoom in and track the defined target automatically.

Protection (IP67, TVS 6000 V)

IP67, TVS 6000 V lightning proof, surge protection, and voltage transient protection.

SMD 4.0

Dahua Smart Motion Detection technology works with intelligent algorithms to classify targets that trigger motion detection alarms. It filters out objects that are not targets, such as small and large animals, to avoid triggering false alarms. With an AI NVR, Quick Pick technology becomes available, allowing you to easily search for and pick out human and vehicle targets from SMD event videos, prioritizing the highest matches.

Technical Specification

Camera

| | |
|----------------------------|---|
| Image Sensor | 1/2.8" CMOS |
| Pixel | 2 MP |
| Max. Resolution | 1920 (H) × 1080 (V) |
| ROM | 4 GB |
| RAM | 1 GB |
| Electronic Shutter Speed | 1/1 s–1/30,000 s |
| Scanning System | Progressive |
| Min. Illumination | Color: 0.005 Lux@F1.6 B/W: 0.0005 Lux@F1.6 0Lux (IR light on) |
| Illumination Distance | 150 m (492.13 ft) |
| Illuminator On/Off Control | Zoom Prio; Manual; Smart IR; Off |
| Illuminator Number | 4 (IR) |

Lens

| | | | | |
|----------------------|--------------------------------------|-------------------------|-------------------------|------------------------|
| Focal Length | 3.95 mm–177.75 mm | | | |
| Max. Aperture | F1.6–F4.95 | | | |
| Field of View | H:65.7°–1.9°V:39.4°–1.1°D:73.1°–2.1° | | | |
| Optical Zoom | 45× | | | |
| Focus Control | Auto; semi-auto; manual | | | |
| Close Focus Distance | 0.1 m–1 m (0.33 ft–3.28 ft) | | | |
| Iris Control | Auto; manual | | | |
| DORI Distance | Detect | Observe | Recognize | Identify |
| | 2451.7 m (8043.64 ft) | 972.9 m (3191.93 ft) | 490.3 m (1608.60 ft) | 245.2 m (804.46 ft) |

PTZ

| | |
|----------------------|---|
| Pan/Tilt Range | Pan: 0° to 360° endless Tilt: –15° to +90°, auto flip 180° |
| Manual Control Speed | Pan: 0.1°/s–300°/s; Tilt: 0.1°/s–200°/s |
| Preset Speed | Pan: 400°/s; Tilt: 300°/s |
| Preset | 300 |
| Tour | 8 (up to 32 presets per tour) |
| Pattern | 5 |
| Scan | 5 |
| Power-off Memory | Yes |
| Idle Motion | Pattern;Preset;Scan;Tour |
| PTZ Protocol | DH-SD Pelco-P/D (auto recognition) |

Intelligence

| | |
|----------------------------|---|
| IVS (Perimeter Protection) | Tripwire; intrusion; climbing fences; loitering detection; abandoned/missing object; fast moving; parking detection; people gathering; vehicle/human alarm classification; linkage tracking |
|----------------------------|---|

Face Detection

Supports face detection, optimization, tracking, capturing pictures, uploading high-quality face snapshots, and face enhancement; Supports attributes extraction. 6 attributes and 8 expressions: Gender, age, glasses, expressions (angry, sad, hate, scary, surprise, calm, happy and confused), mask, mustache; Supports face cutout: Face, one-inch photo. Capturing strategies include real-time capturing, optimization, and quality first.

Auto Tracking

Yes

SMD

Yes

Quick Pick

Yes

Video

| | |
|--------------------------|---|
| Video Compression | H.264H; H.264B; Smart H.265+; H.264; H.265; MJPEG(Sub Stream); Smart H.264+ |
| Streaming Capability | 3 streams |
| Resolution | 1080p (1920 × 1080); 960p (1280 × 960); 720p (1280 × 720); D1 (704 × 576); VGA (640 × 480); CIF (352 × 288) |
| Video Frame Rate | Main stream: 1080P/1.3M/720p@ (1–25/30 fps) Sub stream 1: D1/VGA/CIF@ (1–25/30 fps) Sub stream 2: 720p@ (1–25/30 fps) |
| Bit Rate Control | CBR/VBR |
| Video Bit Rate | H264: 64 kbps–10496 kbps H265: 25 kbps–6400 kbps |
| Day/Night | Auto (ICR)/Color/B/W |
| BLC | Yes |
| WDR | 120 dB |
| HLC | Yes |
| White Balance | Auto/Indoor/Outdoor/Tracking/Manual/Sodium lamp/Natural light/Street lamp |
| Gain Control | Auto/Manual |
| Noise Reduction | 2D/3D |
| Motion Detection | Yes |
| Region of Interest (Rol) | Yes |
| Image Stabilization | Electronic (EIS) |
| Defog | Electronic |
| Digital Zoom | 16× |
| Image Rotation | 180° |
| Privacy Masking | Up to 24 areas can be set, with up to 8 areas in the same view |
| S/N Ratio | ≥ 55 dB |

Audio

| | |
|-------------------|---|
| Audio Compression | PCM; G.711a; G.711Mu; G.726; MPEG2-Layer2; G722.1; G729; G723 |
|-------------------|---|

Network

| | |
|--------------|---------------------------|
| Network Port | 1 × RJ-45 (10/100 Base-T) |
|--------------|---------------------------|

| | |
|---------------------|--|
| Network Protocol | FTP; RTMP; IPv6; Bonjour; IPv4; DNS; RTCP; PPPoE; NTP; RTP; 802.1x; HTTPS; SNMP; TCP/IP; DDNS; UPnP; NFS; ICMP; UDP; IGMP; HTTP; SSL; DHCP; SMTP; Qos; RTSP; ARP |
| Interoperability | ONVIF(Profile S&G&T);CGI;SDK |
| Streaming Method | Unicast/Multicast |
| User/Host | 20 (total bandwidth: 64 M) |
| Storage | Micro SD card (Up to 512 GB); FTP; NAS |
| Browser | IE 9 and later versions Chrome 41 and later versions Firefox 50 and later versions iOS 10 and later versions |
| Management Software | DMSS; DSS Pro |
| Mobile Client | iOS; Android |

Certification

| | |
|----------------|--|
| Certifications | CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014 UL: UL60950-1+CAN/CSA 22.2, No.60950-1 |
|----------------|--|

Port

| | |
|---------------|--|
| Audio Input | 1 channel |
| Audio Output | 1 channel |
| Alarm Linkage | Capture; recording; send email; preset; tour; pattern; alarm digital output |
| Alarm Event | Motion/Tampering detection; audio detection; network disconnection detection; IP conflict detection; memory card state detection; memory space detection |
| Alarm I/O | 2/1 |
| Audio I/O | 1/1 |

Power

| | |
|-------------------|---|
| Power Supply | 24 VDC, 2.5 A ± 25% PoE+ (802.3at) |
| Power Consumption | Basic: 10 W Max: 22 W (illuminator on) |

Environment

| | |
|-----------------------|---|
| Operating Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |
| Operating Humidity | ≤ 95% (RH) |
| Protection | IP67; IK10; TVS 6000V lightning proof; surge protection; voltage transient protection |

Structure

| | |
|--------------------|------------------------------------|
| Product Dimensions | 332 mm × Φ190 mm (13.07" × Φ7.48") |
| Net Weight | 4.7 kg (10.36 lb) |
| Gross Weight | 8.0 kg (17.64 lb) |

Ordering Information

| Type | Model | Description |
|-------------------------|-----------------------|--|
| 2MP WizSense PTZ Camera | DH-SD5A245XA-HNR | 2MP 45x Starlight IR WizSense Network PTZ Camera |
| | SD5A245XA-HNR | 2MP 45x Starlight IR WizSense Network PTZ Camera |
| Accessories | PFB305W | Wall Mount Bracket |
| | DC 24 V/2.5 A | Power Adapter |
| | PFA111 | Mount Adapter |
| | PFA120 | Mount Adapter |
| | PFB300C | Ceiling Mount Bracket |
| | PFA150 | Pole Mount Bracket |
| | PFA151 | Corner Mount Bracket |
| PFB301C | Ceiling Mount Bracket | |

Accessories

Included:



Optional:



Installation

| Wall Mount PFB300W+PFA120 | Ceiling Mount 1 PFA111+PFB300C | Ceiling Mount 2 PFA111+PFB301C |
|---|-----------------------------------|--|
| | | |
| Pole Mount (Vertical) PFB300W+PFA150 | Corner Mount PFB300W+PFA151 | Pole Mount (Horizontal) PFA111+PFB300C+PFA150 |
| | | |

Dimensions (mm [inch])

