

DH-HAC-HDW1400TRQ(-A)

4MP HDCVI IR Eyeball Camera



- Max 30fps@4MP
- Built-in mic (-A)
- CVI/CVBS/AHD/TVI switchable
- 3.6mm fixed lens (2.8mm optional)
- Max. IR length 25m, Smart IR
- IP50, DC12V



System Overview

Experience 4MP full HD video and the simplicity of using existing cabling infrastructure with HDCVI. The Lite series 4MP HDCVI camera features a compact design and offers a high quality image at a friendly price. It offers various motorized/fixed lens models with a multi-language OSD and HD/SD switchable output. Its structural flexibility and high cost-performance makes the camera an ideal choice for SMB solutions.

Functions

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals to be transmitted over 1 coaxial cable simultaneously, i.e. video, audio*, data and power. Dual-way data transmission allows the HDCVI camera to interact with the XVR, such as sending control signal or triggering alarm. Moreover, HDCVI technology supports PoC for construction flexibility.

* Audio input is available for some models of HDCVI cameras.

Long Distance Transmission

HDCVI technology guarantees real-time transmission at long distance without any loss. It supports up to 700 m for 4MP HD video via coaxial cable, and up to 300 m via UTP cable.*

*Actual results verified by real-scene testing in Dahua's test laboratory.

Simplicity

HDCVI technology inherits the feature of simplicity from traditional analog surveillance system, making itself a best choice for investment protection. HDCVI system can seamlessly upgrade the traditional analog system without replacing existing coaxial cabling. The plug and play approach enables full HD video surveillance without the hassle of configuring a network.

Smart IR

The camera is designed with IR LED illumination for best lowlight performance. Smart IR is a technology that ensures brightness uniformity in B/W image under low illumination. Dahua's unique Smart IR adjusts to the intensity of camera's infrared LEDs to compensate for the distance of an object, and prevents IR LEDs from overexposing images as the object come closer to the camera.

Multi-formats

The camera supports multiple video formats including HDCVI, CVBS and other two common HD analog formats in the market. The four formats can be switched over through OSD menu or by PFM820 (UTC controller). This feature makes the camera to be compatible with most end users' existing HD/SD DVRs.

Multi-language OSD

OSD menu provides multiple image adjustments and function settings to meet the requirements of different monitoring scenes. The OSD menu includes configurations such as backlight mode, day/night, white balance, privacy mask and motion detect. The camera supports 11 languages for OSD menu, namely, Chinese, English, French, German, Spanish, Portuguese, Italian, Japanese, Korean, Russian and Polish.

Protection

With working temperature range of -40°C to +50°C (-40°F to 122°F), the camera is designed for extreme temperature environments. Supporting ±30% input voltage tolerance, this camera suits even the most unstable power supply conditions. Its 4KV lightning rating provides protection against the camera and its structure from the effects of lightning.

Technical Specification

Camera	
Image Sensor	1/2.7 inch CMOS
Max. Resolution	2560(H)×1440(V)
Pixel	4MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s–1/100000s NTSC: 1/30s–1/100000s
S/N Ratio	>65dB
Min. Illumination	0.02Lux/F2.0 30IRE, 0Lux IR on
Illumination Distance	25m (82.0 ft)
IR On/Off Control	Auto; manual
Illuminator Number	2 (IR)
Pan/Tilt/Rotation Range	Pan: 0°–360° Tilt: 0°–78° Rotation: 0°–360°

Lens					
Lens Type		Fixed-focal			
Mount Type		M12			
Focal Length		2.8 mm; 3.6 mm			
Max. Aperture		2.8mm: F2.0 3.6mm: F2.0			
Field of View		2.8mm: H: 105°;V: 56°;D: 125° 3.6mm: H: 84°;V: 47°;D:104°			
Iris Type		Fixed iris			
Close Focus Distance		2.8mm: 0.7m(2.30 ft) 3.6mm: 1.1m(3.60 ft)			
DORI Distance	Lens	Detect	Observe	Recognize	Identify
	2.8 mm	49.8m (163.4 ft)	19.9m (65.3 ft)	10m (32.8 ft)	5m (16.4 ft)
	3.6 mm	64m (210.0 ft)	25.6m (84 ft)	12.8m (42 ft)	6.4m (21 ft)

Video	
Frame Rate	CVI: PAL: 4M@25fps; 1080P@25fps; NTSC: 4M@30fps; 1080P@30fps AHD: PAL: 4M@25fps; NTSC: 4M@30fps TVI: PAL: 4M@25fps; NTSC: 4M@30fps CVBS: PAL: 960H; NTSC: 960H
Resolution	4M (2560 × 1440); 1080P (1920 × 1080); 960 H (960 × 576/960 × 480)
Day/Night	Auto switch by ICR
BLC	BLC/HLC/DWDR
WDR	DWDR
White Balance	Auto; manual

Gain Control	Auto; manual
Noise Reduction	2D NR
Smart IR	Yes
Mirror	Off/On
Privacy Masking	Off/On (8 area, rectangle)





















Certifications	CE (EN55032:2015, EN 61000-3-2:2014, EN 61000-3-3:2013, EN55024:2010+A1:2015, EN 55035:2017, EN50130-4:2011+A1:2014) FCC (CFR 47 FCC Part 15 subpartB, ANSI C63.4-2014) UL (UL60950-1+CAN/CSA C22.2 No.60950-1)
----------------	---





Port	
Video Output	Video output choices of CVI/TVI/AHD/CVBS by one BNC port
Audio Interface	Built-in Mic (-A)

Power	
Power Supply	12V ±30% DC
Power Consumption	Max 2.8W (12V DC, IR on)

Environment	
Operating Temperature	-40°C to +50°C (-40°F to 122°F);<95% (non-condensation)
Storage Temperature	-40°C to +50°C (-40°F to 122°F);< 95% (non-condensation)
Protection Grade	IP50

Structure	
Casing	Plastic
Dimensions	Φ97.1 mm × 93.0 mm (Φ3.82" × 3.66")
Net Weight	0.17 Kg (0.37lb))
Gross Weight	0.23 Kg (0.51lb)

Ordering Information			Accessories		
Type	Part Number	Description	Optional:		
4MP Camera	DH-HAC-HDW1400TRQP 2.8 mm	4MP HDCVI IR Eyeball Camera, PAL			
	DH-HAC-HDW1400TRQP 3.6 mm				
	DH-HAC-HDW1400TRQN 2.8 mm	4MP HDCVI IR Eyeball Camera, NTSC			
	DH-HAC-HDW1400TRQN 3.6 mm ;				
	DH-HAC-HDW1400TRQP-A 2.8 mm	4MP HDCVI IR Eyeball Camera, PAL			
	DH-HAC-HDW1400TRQP-A 3.6 mm				
	DH-HAC-HDW1400TRQN-A 2.8mm	4MP HDCVI IR Eyeball Camera, NTSC			
	DH-HAC-HDW1400TRQN-A 3.6mm				
Accessories	PFA13G	Junction Box			
	PFB205W	Wall Mount Bracket			
	PFA152-E	Pole Mount Bracket (For use with PFB205W)			
	PFA130-E	Junction box			
	PFM800-4K	Passive HDCVI Balun			
	PFM321D	12V 1A Power Adapter			
	PFM820 (Only 1080P and below are available)	UTC Controller			
	PFM904	Integrated Mount Tester			

Junction Mount	Wall Mount	Ceiling Mount
		
Pole Mount (Vertical)		
		

Dimensions (mm[inch])

