

DH-HAC-ME1200EQ-L

2MP Smart Dual Light Active Deterrence HDCVI Fixed-focal Eyeball Camera



Series Overview

The Active Deterrence Series offers a multi-dimensional system that links surveillance videos to alarms, audio prompts and various types of information to assist with verifying potential risks. Cameras in this series actively warn off intruders with light and sound, while keeping you up to date of events in real-time through alarm-over-coax and its live view.

Functions

Smart Dual Light

With its smart dual light mechanism, the camera automatically turns on the white light when Perimeter Protection/SMD Plus function of AI XVR detects a target in the rule area to capture clear, vivid images. When the target leaves the rule area, the camera automatically switches over from the white light to the IR light to significantly reduce light pollution.

Active Deterrence (White Light)

Designed with active deterrence technology, the camera turns on a white light and a siren to deter and warn off intruders. The light can be set to flash in intervals or remain solid, and the siren has customizable settings (Only -LS models support siren).

Easy Installation

HDCVI eyeball comes with a quick-to-install pedestal, which makes it easier to install than conventional eyeballs and reduces cost on time and labor.

Protection (IP67, Wide Voltage)

IP67: The camera passed a series of rigorous dust and immersion tests. Its enclosure is both dust-proof and waterproof, and can function normally while being immersed in 1 m deep water for up to 30 minutes

Wide voltage: The camera has $\pm 30\%$ input voltage tolerance (for some power supplies) and a wide voltage range, making it suitable for a variety of outdoor scenarios.

- * The parameters and datasheets below can only be applied to 1200-S6 series.
- * In order to use the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to V1.001.0000000.0.R.20240202 or later version.
- Max. 30 fps@1080p.
- · CVI/CVBS/AHD/TVI switchable
- · Active deterrence with warm light
- · 3.6 mm fixed lens (2.8 mm optional)
- · Super Adapt
- 3D NR
- · Smart Dual Light.
- · 30 m illumination distance.
- · Quick-to-install eyeball save installation time
- · IP67, 12 V DC













Super Adapt

With its intelligent algorithm, the camera automatically adjusts its parameters to provide optimal performance and vivid images.

Advanced 3DNR

Dahua's advanced 3DNR technology reduces image noise with little to no impact on image sharpness, especially in poor lighting conditions. It detects the noise, and compares the sequential frames to effectively reduce the noise. It also makes efficient use of bandwidth, saving on storage space.

Long Distance Transmission

HDCVI technology provides long distance transmission in real time without transmission loss. It supports transmission distances up to 700 m for 2-MP/5-MP/8-MP HD videos through coaxial cables, and up to 300 m through UTP cables. The results were obtained and verified through rigorous testing in Dahua's test laboratory.

4 Signals over 1 Coaxial Cable

HDCVI technology supports 4 signals (video, audio*, data and power) which are simultaneously transmitted over a coaxial cable. Dual-way data transmission allows the HDCVI camera to interact with the XVR to perform various actions such as sending control signals and triggering alarms. HDCVI technology also supports PoC, which makes the camera easy and quick to install.

* Audio input is available for select HDCVI camera models.

Simplicity

HDCVI technology inherits the simplicity of traditional analog surveillance systems, making it a great mechanism for protecting your valuables. HDCVI can be upgraded from the traditional analog system without replacing the existing coaxial cabling. Its plug and play design enables it to produce high-definition videos during surveillance without the hassle of configuring a network.

Technical	Specification	n Dahua					White Balance	Auto;Area white balance
Camera							Gain Control	Auto
Image Sensor		2 MP CMOS				Noise Reduction	3D NR	
Max. Resoluti	on	1920 (H) × 1080 (V)			Illumination Mode	Smart IR&WL WL Mode; IR Mode		
Scanning Syst	em	Progressive					Mirror	Yes
Electronic Shutter Speed		PAL: 1/25 s-1/100,000 s NTSC: 1/30 s-1/100,000 s					PIR	
		0.01 lux@F2.0 (Color, 30 IRE)					Detection Mode	Pyroelectric infrared sensor
Min. Illumination		0.001 lux@F2.0 (B/W, 30 IRE) 0 lux (Illuminator on)					Max. Detection Range	10 m (32.8 ft), 110°
S/N Ratio		>65 dB					Recommended Installation Height	2.2 m-3 m (7.2 ft-9.8 ft)
Illumination Distance		30 m (98.43 ft)				Recommended Working Temperature	10 °C to F0 °C (14 °C to 122 °C)	
Illuminator On/Off Control		Auto;Manual					-10 °C to 50 °C (14 °F to 122 °F)	
Illuminator N	umber	1 (Warm light);1 (IR light)					Active Deterrence	
Angle Adjustment		Pan: 0°–360°; Tilt: 0°–78°; Rotation: 0°–360°					Warm Light Warning	Flash; Alert Duration: 5 s–60 s; flash Freq: low/medium/high
Lens							Certification	
Lens Type		Fixed-focal					Certifications	CE-LVD: EN 62368-1; CE-EMC: EN 55032; EN 55035;
Auto Focus		No					Port	
Lens Mount		M12						Video output choices of CVI/TVI/AHD/CVBS by one BNO
Focal Length		3.6 mm; 2.8 mm					Video Output	port
Max. Aperture		F2.0					Power	
Field of View		2.8 mm: H: 134°; V: 111°; D: 60°					Power Supply	12 VDC ± 30%
Iria Cantual		3.6 mm: H: 108°; V: 89°; D: 48° Fixed					Power Consumption	Max 3.3 W (12 VDC, IR on)
Iris Control		2.8 mm: 0.5 m (1.64 ft)					Environment	
Close Focus Distance		3.6 mm: 0.7 m (2.30 ft)					Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
	Lens	Detect	Observe	Recognize	Identify		Operating Humidity	<95% (RH), non-condensing
DORI Distance	2.8 mm	40.6 m (133.20 ft)	16.2 m (53.15 ft)	8.1 m (26.57 ft)	4.1 m (13.45 ft)		Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
		49.9 m	20.0 m	10.0 m	5.0 m		Storage Humidity	<95% (RH), non-condensing
	3.6 mm	(163.71 ft)	(65.62 ft)	(32.81 ft)	(16.40 ft)		Protection	IP67
ABF		Yes					Anti-corrosion Level	Basic Protection
Video							Structure	
Video Frame Rate		CVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; AHD: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; TVI: PAL: 1080p@25 fps; NTSC: 1080p@30 fps; CVBS: PAL: 960H; NTSC: 960H					Casing Material	Dome (metal + plastic) + plastic enclosure
							Product Dimensions	Φ109.9 mm x 100.9 mm (Φ4.33" x 3.97")
							Net Weight	0.30 kg (0.66 lb)
							Gross Weight	0.47 kg (1.04 lb)
							Installation	Wall mount; ceiling mount; vertical pole mount
Resolution		1080p (1920 x 1080); 960H (960 x 576/960 x 480)						
Day/Night		Auto(ICR)/Color/B/W						
BLC		BLC; HLC; DWDR						
WDR		DWDR						

Active Deterrence Series | DH-HAC-ME1200EQ-L

Ordering Information								
Туре	Model	Description						
	DH-HAC-ME1200EQP-L	2MP Smart Dual Light Active Deterrence HDCVI Fixed- focal Eyeball Camera, PAL						
HDCVI CAMERA	DH-HAC-ME1200EQN-L	2MP Smart Dual Light Active Deterrence HDCVI Fixed- focal Eyeball Camera , NTSC						
	DH-PFB220C	Ceiling Mount Bracket						
	DH-PFA109	Mount adapter						
	DH-PFA13G	Junction box						
	DH-PFA151	Corner mount bracket						
	DH-PFA150	Pole Mount Bracket						
Accessories (Optional)	DH-PFA152-E	Pole Mount Bracket						
	DH-PFB205W-E	Wall Mount Bracket						
	DH-PFM321-EN	DC12V1A power adapter						
	DH-PFM321D-EN	DC12V 1A power adapter						
	DH-PFM320D-EN	DC12V2A power adapter						
	PFM904	Integrated Mount Tester						



Optional:



DH-PFB220C Ceiling Mount Bracket



DH-PFA151 Corner mount bracket



DH-PFA109 Mount adapter



DH-PFA150 Pole Mount Bracket





DH-PFM321-EN



DH-PFA13G

Junction box

DH-PFA152-E

Pole Mount Bracket

DH-PFM321D-EN DC12V1A power adapter DC12V 1A power adapter




DH-PFB205W-E

Wall Mount Bracket

DH-PFM320D-EN DC12V2A power adapter



PFM904 Integrated Mount Tester



Dimensions (mm[inch])

mm [inch]

